



C 213 - Monitor Municipal Wastewater



HI 83213 is a multi-parameter instrument that can also run on common 9V batteries to measure 24 of the most important chemicals and metals in municipal wastewater.

- Microprocessor accuracy and touch-button convenience
- Only 6 keys to perform all measurements
- Can be transported anywhere: runs also on battery power
- 24 different meters and test kits packed into one handy meter
- Large Liquid Crystal Display with self-diagnostic messages
- Built-in RS232 port to download to your PC
- For spare reagent sets see the codes below

Test	Range	Method	Reagent Code
Aluminum	0.00 to 1.00 mg/L	Aluminon	HI 93712-01
Ammonia LR	0.00 to 3.00 mg/L	Nessler	HI 93700-01
Ammonia MR	0.00 to 10.00 mg/L	Nessler	HI 93715-01
Bromine	0.00 to 8.00 mg/L	DPD	HI 93716-01
Chlorine*, Free	0.00 to 2.50 mg/L	DPD	HI 93701-01
Chlorine*, Total	0.00 to 3.50 mg/L	DPD	HI 93711-01
Chromium VI HR	0 to 1000 µg/L	Diphenylcarbohydrazide	HI 93723-01
Chromium VI LR	0 to 300 µg/L	Diphenylcarbohydrazide	HI 93749-01
Color	0 to 500 PCU	Platinum Cobalt	—
Copper HR	0.00 to 5.00 mg/L	Bicinchoninate	HI 93702-01
Copper LR	0 to 1000 µg/L	Bicinchoninate	HI 95747-01
Iodine	0.0 to 12.5 mg/L	DPD	HI 93718-01
Nickel HR	0.00 to 7.00 g/L	Photometric	HI 93726-01
Nickel LR	0.000 to 1.000 mg/L	PAN	HI 93740-01**
Nitrate	0.0 to 30.0 mg/L	Cadmium Reduction	HI 93728-01
Nitrite HR	0 to 150 mg/L	Ferrous Sulphate	HI 93708-01
Nitrite LR	0.00 to 0.35 mg/L	Diazotization	HI 93707-01
Oxygen, Dissolved (D.O.)	0.0 to 10.0 mg/L	Winkler	HI 93732-01
pH	6.5 to 8.5 pH	Phenol Red	HI 93710-01
Phosphate HR	0.0 to 30.0 mg/L	Amino Acid	HI 93717-01
Phosphate LR	0.00 to 2.50 mg/L	Ascorbic Acid	HI 93713-01
Phosphorus	0.0 to 15.0 mg/L	Amino Acid	HI 93706-01
Silver	0.000 to 1.000 mg/L	PAN	HI 93737-01**
Zinc	0.00 to 3.00 mg/L	Zincon	HI 93731-01

* For Chlorine, liquid reagents are available, see section V.

** Reagents for 50 tests

All reagents with -01 final code are for 100 tests.

For a comprehensive list of accessories and reagents, see sections U and V

Specifications

Light Source	4 tungsten lamps with narrow band interference filter 420/525/575/610 nm
Light Detector	4 Silicon Photocells
Power Supply	2 x 9V battery or 12 Vdc adapter
Auto-off	after 10 minutes of non-use
Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing
Dimensions / Weight	230 x 165 x 70 mm / 640 g

Ordering Information

HI 83213 is supplied complete with 3 cuvettes, bottle for D.O. test, batteries, 12 Vdc adapter and instructions.